

Application
for
United States Letters Patent

To all whom it may concern:

Be it known that Yee Mau CHEN and Sum Fat POON
have invented certain new and useful improvements in
SPOON BREWING APPARATUS
of which the following is a full, clear and exact description.

SPOON BREWING APPARATUS**FIELD OF THE INVENTION**

The present invention relates to a brewing filter apparatus
5 designed for measuring the required amount of coffee grounds
or beverage adapted to be mounted on a beverage- or coffee-making
machine for brewing said coffee grounds or beverage under high-
or normal/atmospheric conditions. Particularly, the present
invention relates to filter apparatus adapted for making foam
10 or froth in the brewed beverage or coffee.

BACKGROUND OF THE INVENTION

The aim of this invention is to remedy the problems normally
associated with the brewing of coffee and creating a small
15 bubble foam or froth layer, or brewing coffee without producing
this small bubble foam or froth layer. Typically, coffee
makers which are able to produce coffee with a small bubble
foam layer, require the use of pod or pads, which are prepackaged
coffee grains or grounds with filter paper.

20 The problem faced by the consumer is the reliance on these
coffee pads, which are usually priced at a premium. The coffee
pads themselves are also not as readily available as packaged
ground coffee.

25 The spoon shaped coffee brewing apparatus was shown in U.S.
Patent No. 6,481,338, the content of which is incorporated into
this application by reference, which uses a coffee grounds
measuring spoon to measure the amount of coffee grounds needed
30 per cup of coffee, and use said spoon to brew the coffee. The
spoon also contains exit openings for the brewed coffee.

As measuring spoons are typically used for measuring loose
or fine coffee grounds, there is no added cost of having to
35 purchase coffee pads, nor does the consumer encounter
shortages which occur as a result of the limited supply of
coffee pads.

Since brewing is done in the spoon chamber, contamination of the coffee making machine is very limited and minimal, and the only part the coffee making machine which requires cleaning is the spoon filter.

5

In addition, since brewing is done in the spoon chamber, each coffee drinker can brew different types of coffee grounds consecutively from one machine with their own spoons.

10 However, the less appealing features of the previous design of the spoon shaped coffee brewing apparatus when compared to the present invention are:

1. The spoon apparatus has a seal ring on the top.

15

2. The spoon apparatus requires too many components thereby increasing the size and weight of the apparatus.

3. The design of the spoon apparatus results in excess water
20 being left over the top of the coffee grounds after brewing.

4. The original spoon design requires the use of an unique locking mechanism, such as a hook. However, the present invention can be adapted to use the original locking
25 mechanism as well as the single serve lock mechanism.

The above-described problems make the spoon apparatus clumsy and hard to use.

30 It is the object of the present invention to remedy the problems normally associated with the spoon shaped coffee brewing apparatus. It is another objective of the present invention to provide a brewing filter which is simpler and easier to use or cleaner, and which can be adapted for use in different
35 single-serve coffee machines.

The present invention is easier to assemble and uses fewer components. The present invention also decreases water stay

on top of the coffee inside the brewing chamber of filter apparatus during and/or after brewing. After brewing the coffee, some water will remain on top of the coffee grounds due to the lack of pressure or low pressure exerted on the remaining
5 water which has not passed through the small hole/holes on the brewing chamber of the filter apparatus. In the present invention, the space between the water spreader and the grain coffee is reduced so that less water will stay on top or remain inside brewing chamber of the filter apparatus. The present
10 invention also produces a small bubble foam layer without requiring the use of pods or prepackaged coffee pads.

It is still yet another object of this invention to provide a brewing filter apparatus made out of metal to make it more
15 sturdy and rigid. The top mesh is an optional part of the brewing filter apparatus which is designed to prevent coffee grounds or beverage mixes from sticking to the water spreader and/or the seal ring on the brew head of the coffee machine. When coffee grounds adhere to the seal ring, it will induce leaking.
20 For the user, the mesh can keep the water spreader and seal ring clean, but the use of a mesh is optional.

The foregoing objects and advantages of the present invention are illustrative of those that can be achieved by the present
25 invention and are not intended to be exhaustive or limiting of the possible advantages which can be realized. Thus, these and other objects and advantages of the invention will be apparent from the description herein or can be learned from practicing the invention, both as embodied herein or as modified
30 in view of any variation which may be apparent to those skilled in the art. Accordingly, the present invention resides in the novel methods, arrangements, combinations and improvements herein shown and described.

SUMMARY OF THE INVENTION

In accordance with these and other objects of the invention, a brief summary of the present invention is presented. Some simplifications and omission may be made in the following
5 summary, which is intended to highlight and introduce some aspects of the present invention, but not to limit its scope. Detailed descriptions of a preferred exemplary embodiment adequate to allow those of ordinary skill in the art to make and use the invention concepts will follow in later sections.

10

According to an aspect of the present invention, a new and improved brewing filter apparatus which is designed to measure, receive and brew beverage mix or coffee is disclosed.

15

According to another aspect of the present invention, the brewing filter apparatus comprises a mesh, a filter, a beverage or coffee receiving container, a handle, a coffee outlet nut and a foam maker.

20

The operation of this brewing filter apparatus is very easy and straightforward. The said apparatus is used to scoop up the required amount of coffee grounds or beverage mix. A mesh, which is optional, is place on top of the coffee grounds or beverage mix. The said apparatus is attached to a coffee making
25 machine and locked. The brewing filter apparatus can be adapted to brew coffee or other beverages with or without a foam or froth layer.

30

DETAILED DESCRITPION OF THE FIGURE

The invention relates to a coffee spoon used to brew or extract coffee beverage from coffee grounds. The invention of this concept is shown in Figure 1 to Figure 2.

5

Figure 1 is a cross-sectional illustration of the brewing filter apparatus.

Figure 2 is an exploded view of the brewing filter apparatus.

10

15

DETAILED DESCRITPION OF THE INVENTION

This invention provides a brewing filter apparatus. In an embodiment, the brewing filter apparatus adapted to be mounted on a coffee- or beverage-making machine comprises a handle
5 attached to the receiving or brewing container, a filter, an outlet nut fixed to the receiving or brewing container and a foam maker attached to the outlet nut. In another embodiment, the above-described handle or receiving or brewing container or filter is made of a suitable material. Said material
10 includes but is not limited to stainless steel, plastic or heat-resistant plastic. In a preferred embodiment, the brewing filter apparatus is made of a suitable metal.

In a further embodiment, the receiving/brewing container of
15 the brewing filter apparatus is designed for obtaining and/or measuring the required amount of coffee grounds or beverage mixes needed for making the desire amount of brewed coffee or beverage. The brewing filter apparatus of the present invention can be use to brew beverages including but not limited
20 to tea, chocolate or other flavored beverage mixes.

This invention provides a brewing filter apparatus adapted to be mounted on a coffee- or beverage-making machine, comprising a handle 3 attached to the receiving/brewing
25 container 2, a filter 1, an outlet nut 4 fixed to the receiving/brewing container 1 and a foam maker 5 attached to the outlet nut 4.

In an embodiment, the shape of the brewing filter apparatus
30 or the receiving/brewing container is round, square, oval or rectangular. In a preferred embodiment, the shape of the brewing filter apparatus or the receiving/brewing container is round.

35 The main component of the brewing filter apparatus is the coffee or beverage receiving/brewing container 2. The filter 1 is press fitted or attached using other fitting methods, such as fitting by welding or brazing, to the beverage or coffee

receiving container 2. The filter 1 is used to separate the coffee grounds and the extracted/brewed coffee. The handle 3 is fixed to the beverage or coffee receiving container so that the user can hold the brewing filter apparatus. The outlet nut 4 is riveted to the center of the beverage or coffee receiving container. The outlet nut 4 has one or more small/tiny holes to create jets of brewed coffee or beverage. The size of the said holes on the outlet nut ranges from 0.8mm to 2mm in diameter. The foam maker 5 can make the jets of brewed coffee or beverage become foam. The foam maker 5 is mounted on the outlet nut 4, and jets of brewed coffee or beverage make contact with the bottom of the foam maker thereby creating foam. The foam maker has two or more openings on the foam chamber to let the brewed coffee or beverage and foam flow out. Foam is created because jets of brewed coffee or beverage make contact with the bottom of the foam maker. The openings on the foam maker cannot be located in the center because jets of brewed coffee or beverage need to make contact with a solid surface in order to create foam. The mesh 6 is used to cover the coffee grounds or beverage mixes, but the use of a mesh is optional. The mesh is designed to contain the coffee grounds or beverages mixes within the beverage or coffee receiving container during and after brewing. The mesh can be completely detachable or connected to the beverage or coffee receiving container using a hinge.

In an embodiment of the above apparatus, the brewing filter is adapted or modified for use on various different single serve coffee- or beverage-making machines. This is possible because the sealing component is located on the coffee- or beverage-making machines. The user can just place the coffee grounds or beverage mixes into the beverage or coffee receiving container, place the mesh cover over the coffee grounds or beverage mixes, and insert the brewing filter apparatus into the coffee- or beverage-making machine. The foam and brewed coffee or beverage will then flow out from the brewing filter.

Although the present invention has been described in detail

with particular reference to preferred embodiments thereof,
it should be understood that the invention is capable of other
different embodiments, and its details, including but not
limited to its shape, dimensions or material of construction,
5 are capable of modifications in various obvious aspects. As
is readily apparent to those skilled in the art, variations
and modifications, including the shape, dimensions or material
of construction of the invention can be affected while remaining
within the spirit and scope of the invention. Accordingly,
10 the foregoing disclosure, description and figures are for
illustrative purposes only, and do not in any way limit the
invention, which is defined only by the claims.

15